

TECHNICAL DATASHEET · AGM DEEP CYCLE

12V/110Ah AGM Deep Cycle Battery(M8)

Victron Energy · article number BAT412101085



Valve regulated, maintenance-free flat plate agm battery for deep cycle service in solar, marine and standby systems. Rated 110 Ah at 12 V, measured over a 20 hr discharge at 25 degrees C.

Price on request

AGM Deep Cycle

110 Ah / 12 V

Technical specifications

Article number	BAT412101085
Battery family	AGM Deep Cycle
Nominal voltage	12 V
Rated capacity	110 Ah
Rated capacity basis	20 hr discharge at 25 degrees C
Dimensions (l x w x h)	330 x 171 x 220 mm
Weight	32 kg
Cold cranking amps (0 degrees F)	500 A
Reserve capacity (80 degrees F)	170 min
Technology	Flat plate AGM
Terminals	M8 threaded insert (copper)
Float design life	7-10 years at 20 degrees C
Base model	BAT412101084 (identical cell, different terminal type)

Cycle design life

- 400 cycles at 80% discharge
- 600 cycles at 50% discharge
- 1500 cycles at 30% discharge

All figures are taken from the manufacturer's official GEL and AGM Batteries datasheet (Victron Energy). The full manufacturer document is available on the product page. Figures apply to the battery in new condition at the stated reference temperature.