

TECHNICAL DATASHEET · OUTDOOR AND ARCHITECTURAL LED LIGHTING - GARDENA SERIES

Gardena Garden LED Floodlight 15 LEDs Wall Mounted

EcoSolaris code: ECO-LED-17 · Designed and manufactured in Europe · OSRAM LEDs



Ornamental garden floodlight with 15 OSRAM LEDs of 0.65 W (10 W total), powder-coated aluminium housing and clear polycarbonate diffuser. Stainless steel bracket for mounting on vertical surfaces. IP66 protection, class III, 230 V supply through an external power unit.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Housing material	Powder-coated aluminium
Diffuser	Clear polycarbonate
Mounting bracket	Stainless steel
Housing colour	Other colours on customer request
Light source	OSRAM LEDs
Number of LEDs	15
Power per LED	0.65 W
Total power	10 W
Efficacy	min. 100 lm/W (white LEDs)
CRI	80 (neutral / warm white), 70 (cool white)
Supply	230 V, 50/60 Hz, external power unit
Cable length	2 m
Insulation class	III
Ingress protection	IP66
Operating temperature	-20 degrees C to +40 degrees C
Dimensions	220 x 160 mm
Weight	1.4 kg
Markings	CE, F-Mark, outdoor use

Features

- 15 OSRAM LEDs of 0.65 W each, 10 W total
- Efficacy of at least 100 lm/W in white light
- CRI 80 in warm and neutral white, 70 in cool white
- IP66 protection for optics and driver
- Class III, 230 V supply through an external power unit
- Painted aluminium housing, stainless steel bracket, vertical mounting
- Operation from -20 degrees C to +40 degrees C

Recommended applications

Garden lighting

Residential spaces

Commercial spaces

Public spaces