

TECHNICAL DATASHEET · OUTDOOR AND ARCHITECTURAL LED LIGHTING - MICRO SERIES

Micro LED Wall Light 1-3 LEDs IP44 Outdoor

EcoSolaris code: ECO-LED-223 · Designed and manufactured in Europe · OSRAM LEDs



General lighting wall fitting with 1, 2 or 3 OSRAM LEDs (2.5 / 5 / 7.5 W), UV-resistant plastic housing and glass diffuser. Omnidirectional distribution, insulation class II, power unit included. Ingress protection IP44, available to IP65 on request. Supply 230 V AC or 12-24 V DC.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Housing material	UV-resistant plastic
Housing colour	Grey as standard
Diffuser	Clear glass
Light source	OSRAM LEDs
Number of LEDs	1 / 2 / 3
Total power	2.5 W / 5 W / 7.5 W
LED colour	Warm white 3000 K / neutral 4000 K / cool 5000 K
Beam focus	Omnidirectional
Efficacy	min. 100 lm/W (white LEDs)
CRI	80 (neutral / warm white), 70 (cool white)
Supply	230 V AC standard or 12-24 V DC
Power unit	Included, inside the housing
Cable length	2 m
Insulation class	II
Ingress protection	IP44 (IP65 optional)
Operating temperature	-20 degrees C to +40 degrees C
Dimensions	230 x 230 x 49 mm
Weight	0.6 kg

Features

- 1-3 OSRAM LEDs, 2.5-7.5 W
- Omnidirectional distribution for general lighting
- Minimum 100 lm/W in white light, CRI 80/70
- IP44 as standard, IP65 on request
- Insulation class II through the enclosure
- 230 V AC or 12-24 V DC, power unit included
- UV-resistant plastic housing, 0.6 kg

Recommended applications

Warehouse lighting

Perimeter lighting

Production area lighting

Garages and cellars