

TECHNICAL DATASHEET · INDUSTRIAL LED FLOODLIGHTS - APOLO II SERIES

Apolo II Industrial LED Floodlight 1 COB LED 30-50W

EcoSolaris code: ECO-LED-304 · Designed and manufactured in Europe · OSRAM LEDs



Compact version of the series: 1 Bridgelux COB LED, 30-50W, minimum 110 lm/W, a 270 x 135 x 150 mm extruded aluminium body with electrostatic paint, 2.5 kg. Driver included, power factor above 0.95, IP66, IK10, class I. Optional emergency kit with 2.5 hours autonomy.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Body material	Extruded aluminium, electrostatically painted
Diffuser	Clear polycarbonate, UV protected
Body colour	Other colours available on request
Light source	1 Bridgelux COB LED
Total power	30-50W
Luminous efficacy	Min. 110 lm/W
LED colour	Neutral white 4000 K / Cool white 5000 K
Beam	Wide / Medium / Narrow
Colour rendering index	80 (neutral white), 70 (cool white)
Supply	Standard 230V AC; 90-230V AC, 50-60Hz
Driver	Included, inside the housing
Emergency kit	Optional, 2.5 hours
Power factor	> 0.95
Insulation class	I
Ingress protection	IP66
Impact resistance	IK10
Operating temperature	-20 degrees C to +40 degrees C
Rotation	plus/minus 45 degrees
Dimensions	270 x 135 x 150 mm
Weight	2.5 kg

Features

- 1 Bridgelux COB LED, minimum 110 lm/W
- Compact 270 mm body, 2.5 kg
- Optional emergency kit, 2.5 hours
- Wide, medium or narrow beam
- IP66, IK10, -20 degrees C to +40 degrees C
- Power factor above 0.95, class I
- plus/minus 45 degrees rotation, suspended or surface fixing

Recommended applications

Warehouse lighting

Production area lighting

Sports field lighting

