

TECHNICAL DATASHEET · LED SAFETY LIGHTING · PROTECT SERIES

LS-09 Recessed LED Safety Luminaire without Emergency Kit

EcoSolaris code: ECO-LED-345 · Designed and manufactured in Europe · OSRAM LEDs



Safety luminaire without emergency kit, recessed into a vertical plasterboard wall. Four high-power OSRAM LEDs in cool white 5000K, polycarbonate diffuser with a customisable pictogram film. White aluminium housing, IP40, electrical protection class III, 230V AC supply.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Housing material	Electrostatically painted aluminium
Housing colour	White (standard)
Diffuser	Clear polycarbonate with pictogram film
Power supply	230V AC, 50Hz
Emergency kit	Not included
Number of LEDs	4 (OSRAM)
LED colour	Cool white 5000K
Beam focus	Omnidirectional
Ingress protection	IP40
Electrical protection class	III
Operating temperature	-20 degrees C to +40 degrees C
Mounting	Recessed in a vertical wall (plasterboard)
Dimensions	300 x 100 x 75 mm
Weight	0.5 kg
Compliance	CE, F-Mark

Features

- 4 high-power OSRAM LEDs, cool white 5000K
- No emergency kit, for central safety systems
- Recessed mounting in a vertical wall
- Electrical protection class III
- IP40 ingress protection, indoor use
- Electrostatically painted white aluminium housing
- Customisable pictogram film
- Designed and made in Europe

Recommended applications

Offices Schools Hospitals Safety lighting