

TECHNICAL DATASHEET · COMMERCIAL LED LIGHTING - CELEST II SERIES

Celest II LED Track Spotlight 1 COB LED 30W

EcoSolaris code: ECO-LED-371 · Designed and manufactured in Europe · OSRAM LEDs



Indoor accent spotlight with a single 30W Bridgelux COB LED, mounted on a 2 m track with 3 circuits. Aluminium body for heat dissipation, plexiglass diffuser, reflector focusing (wide, medium, narrow) and colour temperatures of 3000, 4000 or 5000 K.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Housing material	Anodised aluminium and PVC; external parts in stainless steel
Housing colour	White (standard)
Diffuser	Plexiglass
Light source	1 Bridgelux COB LED
Power per LED	30W
LED colour (option)	Warm white 3000 K / Neutral white 4000 K / Cool white 5000 K
Colour rendering	On request, CRI above 90
Focusing (option)	Wide / Medium / Narrow
Mounting	On a 2 m track with 3 circuits
Nominal current	Max. 16A per track
Power supply	230V AC, 50Hz (standard)
Electrical protection class	I
Ingress protection	IP40
Operating temperature	-20 to +40 degrees C
Dimensions	Diameter 115 mm, length 160 mm
Weight	1 kg
Markings	CE, F-Mark, indoor

Features

- 30W Bridgelux COB LED with reflector focusing
- Three colour temperatures: 3000 K, 4000 K, 5000 K; CRI above 90 on request
- Mounting on a 2 m track with 3 circuits, maximum 16A per track
- Aluminium body for thermal management
- 230V AC supply, class I
- IP40, operation between -20 and +40 degrees C
- Diameter 115 mm, length 160 mm, 1 kg

Recommended applications

Display area lighting

Window displays

Commercial accent lighting