

TECHNICAL DATASHEET · INTERIOR LED LIGHTING - OAZIS SERIES

## Oasis LED Wall Light for Bathrooms and Wet Areas 10-20W

EcoSolaris code: ECO-LED-46 · Designed and manufactured in Europe · OSRAM LEDs



Wall light with chromed metal body and satin glass diffuser, with a protected optical compartment for humid rooms. Samsung LEDs at minimum 100 lm/W, 10W (250 x 90 x 70 mm) or 20W (400 x 90 x 70 mm), internal driver, 90-230V AC supply, class I, IP42.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

### Technical specifications

|                        |                                                 |
|------------------------|-------------------------------------------------|
| Body material          | Chromed metal                                   |
| Diffuser               | Satin glass                                     |
| Body colour            | Standard grey                                   |
| Light source           | Samsung LEDs                                    |
| Total power            | 10W   20W                                       |
| Luminous efficacy      | Min. 100 lm/W                                   |
| Colour rendering index | 80 (neutral white, warm white), 70 (cool white) |
| Supply                 | 230V AC, 50Hz; 90-230V AC                       |
| Driver                 | Internal                                        |
| Insulation class       | I                                               |
| Ingress protection     | IP42                                            |
| Operating temperature  | -20 degrees C to +40 degrees C                  |
| Dimensions             | 400 x 90 x 70 mm / 250 x 90 x 70 mm             |
| Weight                 | 0.7 kg                                          |
| Markings               | CE, F-Mark; indoor                              |

### Features

- Protected optical compartment for bathrooms and kitchens
- Samsung LEDs, minimum 100 lm/W
- Two versions: 10W at 250 mm, 20W at 400 mm
- Chromed metal body with satin glass diffuser
- Internal driver, 90-230V AC, class I
- Operates between -20 degrees C and +40 degrees C
- Designed and manufactured in Europe

### Recommended applications

Bathroom lighting

Interior lighting