

TECHNICAL DATASHEET · RGB DMX LED LIGHTING - GALAXY SERIES

Galaxy Linear RGB DMX LED Floodlight 9 LEDs

EcoSolaris code: ECO-LED-47 · Designed and manufactured in Europe · OSRAM LEDs



Outdoor linear RGB floodlight with 9 OSRAM LEDs (3 x red 650 nm, 3 x green 523 nm, 3 x blue 470 nm) and a DMX driver integrated in the housing. Standard supply 230V AC 50Hz, optional 12-24V DC. Ingress protection IP66, CE and F marking.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Luminaire type	Linear RGB floodlight, Galaxy series
Number of LEDs	9 (3 x red, 3 x green, 3 x blue)
Light source	OSRAM LEDs
LED colour	Red 650 nm, green 523 nm, blue 470 nm
Standard supply	230V AC, 50Hz
Optional supply	12-24V DC power supply
DMX driver	Included, inside the housing
Beam	Wide / medium / narrow / omnidirectional
Ingress protection	IP66
Use	Outdoor
Markings	CE, F

Features

- 9 OSRAM RGB LEDs controlled over DMX
- DMX driver fitted in the housing
- Selectable beam: wide, medium, narrow, omnidirectional
- 230V AC supply as standard, 12-24V DC on request
- IP66 protection for outdoor use
- Direct mounting on normally flammable surfaces (F marking)

Recommended applications

Facade lighting

Architectural lighting

Garden lighting

Access path lighting

Park lighting