

TECHNICAL DATASHEET · RGB DMX LED LIGHTING - GALAXY SERIES

Galaxy Linear RGB DMX LED Floodlight 24 LEDs

EcoSolaris code: ECO-LED-49 · Designed and manufactured in Europe · OSRAM LEDs



Outdoor linear RGB floodlight with 24 OSRAM LEDs (8 x red 650 nm, 8 x green 523 nm, 8 x blue 470 nm) and an integrated DMX driver. Standard supply 230V AC 50Hz or a 12-24V DC power supply. Wide, medium or narrow beam. IP66, CE and F marking.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Luminaire type	Linear RGB floodlight, Galaxy series
Number of LEDs	24 (8 x red, 8 x green, 8 x blue)
Light source	OSRAM LEDs
LED colour	Red 650 nm, green 523 nm, blue 470 nm
Standard supply	230V AC, 50Hz
Optional supply	12-24V DC power supply
DMX driver	Included, inside the housing
Beam	Wide / medium / narrow
Ingress protection	IP66
Use	Outdoor
Markings	CE, F

Features

- 24 OSRAM RGB LEDs in a linear layout
- DMX addressable, driver inside the housing
- Three beams: wide, medium, narrow
- 230V AC or 12-24V DC supply
- Ingress protection IP66
- F marking for mounting on normally flammable surfaces

Recommended applications

Facade lighting

Architectural lighting

Garden lighting

Park lighting

Access path lighting