

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - DISPLAY LINE III SERIES

Display Line III Surface-Mounted Linear LED Luminaire 2 Modules 26W

EcoSolaris code: ECO-LED-56184 · Designed and manufactured in Europe · OSRAM LEDs



Surface-mounted linear LED luminaire with 2 modules, 617 x 59 x 68.5 mm, 26 W, flux 3184-3399 lm, efficacy 122-130 lm/W. Anodised white RAL9010 extruded aluminium profile, clear or multiprismatic diffuser, IP40, IK10, class I, driver included. CCT 3000, 4000 or 5000 K, CRI 80.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Surface mounted
Material	Extruded aluminium
Colour	Anodised white RAL9010
Number of modules	2
Power	26 W
Luminous flux	3184 - 3399 lm
Luminous efficacy	122 - 130 lm/W
Optical efficiency	86.2 - 92.1 %
Diffuser	Clear or multiprismatic
CCT	3000 K / 4000 K / 5000 K
CRI	80
Control	on/off
Ingress protection	IP40
Impact resistance	IK10
Electrical class	I
Driver included	Yes
Adjustable	No
Dimensions	617 x 59 x 68.5 mm

Features

- 617 mm length for standard shelving
- Up to 3399 lm and 130 lm/W
- Clear or multiprismatic diffuser
- Anodised extruded aluminium, IK10
- Driver included, surface mounting
- Class I, IP40, three CCTs

Recommended applications

Retail shelving

Counters

Offices

Workshops and laboratories

Supermarkets