

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - DISPLAY LINE III SERIES

Display Line III Surface-Mounted Linear LED Luminaire 5 Modules 65W

EcoSolaris code: ECO-LED-56230 · Designed and manufactured in Europe · OSRAM LEDs



Surface-mounted linear LED luminaire with 5 modules, 1585 x 59 x 68.5 mm, 65 W, flux 7959-9496 lm, efficacy 122-131 lm/W. Anodised white RAL9010 extruded aluminium profile, clear or multiprismatic diffuser, IP40, IK10, class I, driver included. CCT 3000, 4000 or 5000 K, CRI 80.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Surface mounted
Material	Extruded aluminium
Colour	Anodised white RAL9010
Number of modules	5
Power	65 W
Luminous flux	7959 - 9496 lm
Luminous efficacy	122 - 131 lm/W
Optical efficiency	86.2 - 92.1 %
Diffuser	Clear or multiprismatic
CCT	3000 K / 4000 K / 5000 K
CRI	80
Control	on/off
Ingress protection	IP40
Impact resistance	IK10
Electrical class	I
Driver included	Yes
Adjustable	No
Dimensions	1585 x 59 x 68.5 mm

Features

- Long 1585 mm body, a single driver
- Up to 9496 lm and 131 lm/W
- Clear or multiprismatic diffuser
- Anodised extruded aluminium, IK10
- Three colour temperatures
- Class I, IP40, surface mounting

Recommended applications

Supermarket shelf runs

DIY stores

Warehouses

Production workshops

Laboratories and corridors