

TECHNICAL DATASHEET · EXTERIOR ARCHITECTURAL LIGHTING - GALAXY SERIES

Galaxy 10 Adjustable Linear LED Luminaire 15-26W Outdoor

EcoSolaris code: ECO-LED-56409 · Designed and manufactured in Europe · OSRAM LEDs



Outdoor linear luminaire in extruded aluminium, 83x58x377 mm, with integral driver and 220-240 V AC supply. Available at 15 W or 26 W, with six optics, three colour temperatures and on/off, 1-10V or DALI control. IP66 protection, IK10 impact resistance, insulation class I.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Surface mounted, adjustable (ceiling, floor, wall)
Material	Extruded aluminium
Colours	RAL7040 anodised silver, RAL7040 powder-coated grey, RAL9010 anodised black
Power	15 W / 26 W
Luminous flux	1660-1947 lm (15 W), 3118-3768 lm (26 W)
Luminous efficacy	108-131 lm/W
Optics	Wide, medium, narrow, elliptical, wall grazing, wall washer
Colour temperature	3000 K / 4000 K / 5000 K
CRI	80
Control	on/off, 1-10V, DALI
Ingress protection	IP66 / IK10
Insulation class	I
Power supply	220-240 V AC, driver included
Dimensions	83x58x377 mm
Mounting bracket	BK (-50 degrees / +90 degrees) or standard adjustable (-90 degrees / +90 degrees)
Options on request	RGB with DMX, single colour (red, amber, blue, green)

Features

- Linear profile of 377 mm, adjustable in the horizontal plane
- Six optics, including wall grazing and wall washer
- Efficacy up to 131 lm/W
- IP66 and IK10 for outdoor use
- Driver included in the housing, 220-240 V AC
- On/off, 1-10V or DALI control
- Three RAL finishes, anodised or powder-coated

Recommended applications

Building facades

Columns and parapets

Retaining walls

Gardens and squares

Decorative architectural features