

TECHNICAL DATASHEET · EXTERIOR ARCHITECTURAL LIGHTING - GALAXY SERIES

Galaxy 10 1m Adjustable Linear LED Luminaire 15-26W Outdoor

EcoSolaris code: ECO-LED-56460 · Designed and manufactured in Europe · OSRAM LEDs



Outdoor linear LED luminaire, 1000 x 83 x 58 mm, adjustable in the horizontal plane, 15 or 26 W, 1660 to 3768 lm, 108 to 131 lm/W. Extruded aluminium, IP66, IK10, class I, driver in the housing, 220 to 240 V AC. Six optics, CCT 3000 to 5000 K, CRI 80, DALI, 1-10V or on/off. RGB DMX on request.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Ceiling, floor or wall, adjustable
Mounting bracket	BK (-50 degrees / +90 degrees, metal end caps) or standard (-90 degrees / +90 degrees, plastic end caps)
Material	Extruded aluminium
Colours available	Anodised silver RAL7040, powder-coated grey RAL7040, anodised black RAL9010
Power range	15 - 26 W
Luminous flux	1660 - 3768 lm
Luminous efficacy	108 - 131 lm/W
Optical efficiency	75.5 - 89.7 %
Optics available	Wide, medium, narrow, elliptical, wall grazing, wall washer
CCT	3000 K / 4000 K / 5000 K
CRI	80
Control	DALI, 1-10V, on/off
Supply voltage	220 - 240 V AC
Ingress protection	IP66
Impact resistance	IK10
Insulation class	I
Driver included	Yes, in the housing
Adjustable	Yes, in the horizontal plane
Dimensions	83 x 58 x 1000 mm
Options	RGB with DMX control; single colour (red, amber, blue, green) on request

Features

- One metre profile, adjustable, with two bracket systems
- Six optics, including wall grazing and wall washer
- Efficacy up to 131 lm/W
- IP66, IK10, extruded aluminium in three finishes
- Driver in the housing, DALI, 1-10V or on/off control
- RGB DMX or single colour version on request

Recommended applications

Building facades

Parapets and walkways

Columns and retaining walls

Boundary walls and paths

Dynamic RGB lighting

