

TECHNICAL DATASHEET · EXTERIOR ARCHITECTURAL LIGHTING - ANDROMEDA SERIES

Andromeda 6 Adjustable LED Floodlight 8-14W Outdoor

EcoSolaris code: ECO-LED-56616 · Designed and manufactured in Europe · OSRAM LEDs



Compact adjustable LED floodlight for outdoor accents. 8 to 14.3 W, 864 to 1823 lm, 108 to 127 lm/W. Extruded aluminium housing of 123 x 135 x 170 mm, IP66, IK10, integral driver. Four optics, 3000/4000/5000 K, on/off, DALI or 1-10V control, optional pole mounting bracket.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Adjustable floodlight, surface or pole mounted
Housing material	Extruded aluminium
Colour	Black (RAL9010)
Power range	8 W - 14.3 W
Luminous flux	864 - 1823 lm
Luminous efficacy	108 - 127 lm/W
Optics available	Wide, medium, narrow, elliptical
Colour temperature	3000 K / 4000 K / 5000 K
CRI	80
Control	On/off, DALI, 1-10V
Ingress protection	IP66
Impact resistance	IK10
Electrical insulation class	I
Driver	Included, integrated in the housing
Adjustable	Yes
Available accessories	Pole mounting bracket
Dimensions	123 x 135 x 170 mm

Features

- Compact body of 123 x 135 x 170 mm
- Luminous flux 864 - 1823 lm at 8 - 14.3 W
- Efficacy up to 127 lm/W
- Four optics: wide, medium, narrow, elliptical
- IP66 and IK10 for outdoor use
- Driver integrated in the housing
- Pole mounting bracket available as an accessory

Recommended applications

Gardens and paths

Terraces

Columns and trees

Outdoor display windows

Facade accents