

TECHNICAL DATASHEET · EXTERIOR ARCHITECTURAL LIGHTING - ANDROMEDA SERIES

Andromeda 12 Adjustable LED Floodlight 14.7-28.8W Outdoor

EcoSolaris code: ECO-LED-56651 · Designed and manufactured in Europe · OSRAM LEDs



Adjustable outdoor floodlight of 250x135x170 mm in black extruded aluminium, with integral power supply and pole mounting bracket. 14.7 W and 28.8 W, 1672-3491 lm, 106-129 lm/W. Four optics, CCT 3000-5000 K, on/off, 1-10V or DALI control. IP66, IK10, class I.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Adjustable, pole mounted
Material	Extruded aluminium
Colour	RAL9010 black
Power	14.7 W / 28.8 W
Luminous flux	1672-1904 lm (14.7 W), 3038-3491 lm (28.8 W)
Luminous efficacy	106-129 lm/W
Optics	Narrow, medium, wide, elliptical
Colour temperature	3000 K / 4000 K / 5000 K
CRI	80
Control	on/off, 1-10V, DALI
Ingress protection	IP66 / IK10
Insulation class	I
Power supply	Integrated in the housing
Dimensions	250x135x170 mm
Adjustable	Yes

Features

- Adjustable floodlight with pole mounting
- Four optics: narrow, medium, wide, elliptical
- Efficacy of 106-129 lm/W
- Integral power supply
- IP66 and IK10, extruded aluminium
- On/off, 1-10V or DALI control

Recommended applications

Building facades

Monuments and statues

Ornamental trees

Signage panels

Parks and company yards