

TECHNICAL DATASHEET · EXTERIOR ARCHITECTURAL LIGHTING - ANDROMEDA SERIES

Andromeda 24 Adjustable LED Floodlight 29.4-57.6W Outdoor

EcoSolaris code: ECO-LED-56686 · Designed and manufactured in Europe · OSRAM LEDs



Adjustable outdoor floodlight of 437x135x170 mm in black extruded aluminium, with integral power supply and pole mounting bracket. 29.4 W and 57.6 W, 3345-7299 lm, 113-130 lm/W. Four optics, CCT 3000-5000 K, on/off, 1-10V or DALI control. IP66, IK10, class I.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Adjustable, pole mounted
Material	Extruded aluminium
Colour	RAL9010 black
Power	29.4 W / 57.6 W
Luminous flux	3345-3808 lm (29.4 W), 6472-7299 lm (57.6 W)
Luminous efficacy	113-130 lm/W
Optics	Narrow, medium, wide, elliptical
Colour temperature	3000 K / 4000 K / 5000 K
CRI	80
Control	on/off, 1-10V, DALI
Ingress protection	IP66 / IK10
Insulation class	I
Power supply	Integrated in the housing
Dimensions	437x135x170 mm
Adjustable	Yes

Features

- Output up to 7299 lm at 57.6 W
- Efficacy of 113-130 lm/W
- Adjustable, with pole mounting
- Four optics for facades, walls and aprons
- Integral power supply, IP66 and IK10
- On/off, 1-10V or DALI control

Recommended applications

Multi-storey facades

Heritage monuments

Small sports pitches

Car parks and yards

Industrial courtyards