

TECHNICAL DATASHEET · EXTERIOR ARCHITECTURAL LIGHTING - ANDROMEDA SERIES

Andromeda 36 Adjustable LED Floodlight 44-86W Outdoor

EcoSolaris code: ECO-LED-56721 · Designed and manufactured in Europe · OSRAM LEDs



Adjustable outdoor floodlight for facades and large surfaces. 44.1 to 86.4 W, 5016 to 10473 lm, 106 to 129 lm/W. Extruded aluminium housing, IP66, IK10, integral power supply. Four optics and on/off, DALI or 1-10V control.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Adjustable outdoor floodlight
Housing material	Extruded aluminium
Colour	Black (RAL9010)
Power range	44.1 W - 86.4 W
Luminous flux	5016 - 10473 lm
Luminous efficacy	106 - 129 lm/W
Optics available	Wide, medium, narrow, elliptical
Colour temperature	3000 K / 4000 K / 5000 K
CRI	80
Control	On/off, DALI, 1-10V
Ingress protection	IP66
Impact resistance	IK10
Electrical insulation class	I
Driver	Included, integrated in the housing
Adjustable	Yes
Dimensions	405 x 260 mm

Features

- Luminous flux up to 10473 lm at 86.4 W
- Luminous efficacy up to 129 lm/W
- Four beam distributions: narrow, medium, wide, elliptical
- IP66 ingress protection and IK10 impact resistance
- Power supply integrated in the housing
- On/off, DALI or 1-10V control
- Adjustable extruded aluminium body

Recommended applications

Building facades

Monuments and walls

Industrial halls

Car parks

Exterior architectural lighting