

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - INDUSTRIAL FLOODLIGHTS - TITAN SERIES

Titan 12 Industrial LED Floodlight 60W Indoor

EcoSolaris code: ECO-LED-56752 · Designed and manufactured in Europe · OSRAM LEDs



60 W industrial floodlight with an extruded aluminium housing of 167 x 150 x 306 mm, integral power supply and power factor above 0.95. Flux 7336-7744 lm and efficacy 123-129 lm/W in five distributions (narrow, medium, wide, extra wide, street) at 4000 K or 5000 K. IP66/IK10 protection, insulation class I, adjustable bracket for flat surfaces or poles.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Flat surface or pole, adjustable
Material	Extruded aluminium
Finish	Grey RAL7040, electrostatic powder coated
Power	60 W
Luminous flux	7336-7744 lm
Luminous efficacy	123-129 lm/W
Optics	Narrow, medium, wide, extra wide, street
Colour temperature	4000 K / 5000 K
CRI	80
Control	on/off
Power factor	> 0.95
Ingress protection	IP66 / IK10
Insulation class	I
Driver included	Yes
Dimensions	167 x 150 x 306 mm

Features

- Efficacy up to 129 lm/W
- Five light distributions
- IP66 and IK10
- Power factor above 0.95
- Integral power supply, insulation class I
- Adjustable mounting bracket

Recommended applications

Production halls

Warehouses and logistics

Workshops

Covered car parks

Internal ramps and driveways