

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - TITAN SERIES

Titan 24 Adjustable Industrial LED Floodlight 120W

EcoSolaris code: ECO-LED-56791 · Designed and manufactured in Europe · OSRAM LEDs



Adjustable 120 W industrial LED floodlight with a grey RAL7040 extruded aluminium housing, IP66, IK10, class I. Flux 14672-15487 lm, efficacy 122-129 lm/W, five optics including street and extra wide. CCT 4000 K or 5000 K, CRI 80, integrated driver, power factor above 0.95.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	On a flat surface or on a pole
Material	Extruded aluminium
Colour	Grey RAL7040, electrostatically coated
Power	120 W
Luminous flux	14672 - 15487 lm
Luminous efficacy	122 - 129 lm/W
Optical efficiency	93.2 - 98.3 %
Available optics	Wide, medium, narrow, extra wide, street
CCT	4000 K / 5000 K
CRI	80
Power factor	> 0.95
Control	on/off
Ingress protection	IP66
Impact resistance	IK10
Electrical class	I
Driver included	Yes
Adjustable	Yes
Dimensions	167 x 150 x 445 mm

Features

- Up to 15487 lm and 129 lm/W
- Five optics, including street and extra wide
- Extruded aluminium housing, IP66, IK10
- Adjustable, surface or pole mounting
- Integrated driver, class I, PF above 0.95
- Grey RAL7040 electrostatic coating

Recommended applications

Production halls

Warehouses

Loading bays

Car parks and yards

Internal roads on poles