

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - TITAN SERIES

Titan 36 Adjustable Industrial LED Floodlight 180W

EcoSolaris code: ECO-LED-56826 · Designed and manufactured in Europe · OSRAM LEDs



Adjustable 180 W industrial LED floodlight with a 616 mm grey RAL7040 extruded aluminium housing, IP66, IK10, class I. Flux 22008-23231 lm, efficacy 122-129 lm/W, five optics. CCT 4000 K or 5000 K, CRI 80, integrated driver, power factor above 0.95, surface or pole mounting.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	On a flat surface or on a pole
Material	Extruded aluminium
Colour	Grey RAL7040, electrostatically coated
Power	180 W
Luminous flux	22008 - 23231 lm
Luminous efficacy	122 - 129 lm/W
Optical efficiency	93.2 - 98.3 %
Available optics	Wide, medium, narrow, extra wide, street
CCT	4000 K / 5000 K
CRI	80
Power factor	> 0.95
Control	on/off
Ingress protection	IP66
Impact resistance	IK10
Electrical class	I
Driver included	Yes
Adjustable	Yes
Dimensions	167 x 150 x 616 mm

Features

- Up to 23231 lm from 180 W
- Efficacy 122-129 lm/W
- Five optics, street version for pole mounting
- IP66, IK10, coated extruded aluminium
- Adjustable, integrated driver, class I
- Power factor above 0.95

Recommended applications

High bays

Logistics terminals

Outdoor storage yards

Car parks and perimeters

Internal roads