

TECHNICAL DATASHEET · EXTERIOR ARCHITECTURAL LIGHTING - STREET LED LUMINAIRES - TOPAZ SERIES

Topaz 24 Street LED Luminaire 120W

EcoSolaris code: ECO-LED-56904 · Designed and manufactured in Europe · OSRAM LEDs



120 W pole-mounted street luminaire with an extruded aluminium housing of 586 x 248 x 63 mm and an adjustable bracket. Flux 14672-15487 lm, efficacy 122-129 lm/W, with street, narrow, medium, wide or extra wide distributions at 4000 K or 5000 K, CRI 80. IP66/IK10 protection, insulation class I, driver included, on/off control.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Pole mounted, adjustable
Material	Extruded aluminium
Finish	Grey RAL7040, electrostatic powder coated
Power	120 W
Luminous flux	14672-15487 lm
Luminous efficacy	122-129 lm/W
Optics	Street, narrow, medium, wide, extra wide
Colour temperature	4000 K / 5000 K
CRI	80
Control	on/off
Ingress protection	IP66 / IK10
Insulation class	I
Driver included	Yes
Dimensions	586 x 248 x 63 mm

Features

- Up to 15487 lm and 129 lm/W
- Dedicated street optic plus four alternative distributions
- Extruded aluminium housing, IP66 / IK10
- Adjustable pole mounting bracket
- 4000 K or 5000 K
- Driver included, insulation class I

Recommended applications

Streets and boulevards

Estate roads

Car parks

Logistics yards

Industrial perimeters