

TECHNICAL DATASHEET · EXTERIOR ARCHITECTURAL LIGHTING - LINEAR LUMINAIRES - LINEA SERIES

Linea N Flexible LED Neon 7.2W Outdoor IP67

EcoSolaris code: ECO-LED-56943 · Designed and manufactured in Europe · OSRAM LEDs



Flexible neon cast in silicone, 15 x 15 mm, supplied in 5000 mm lengths, with 168 LEDs per metre and omnidirectional emission. Power 7.2 W, flux 440 lm, CRI above 90, colour temperature 3000 K or 4000 K. Cut every 7 LEDs (41.6 mm), minimum bend radius 60 mm, IP67/IK10 protection. Driver not included; a 1 m aluminium profile is available as an accessory.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	In a 1 m aluminium profile (accessory) or directly on the substrate
Material	Cast silicone
Finish	Grey RAL7040
Power	7.2 W
Luminous flux	440 lm
Luminous efficacy	60.54 lm/W
Distribution	Omnidirectional
LED count	168 LED/m
Minimum cutting length	7 LEDs / 41.6 mm
Bend radius	Minimum 60 mm
Colour temperature	3000 K / 4000 K
CRI	> 90
Control	on/off, dimming
Ingress protection	IP67 / IK10
Insulation class	I
Driver included	No
Dimensions	15 x 15 x 5000 mm

Features

- 168 LEDs per metre, continuous line with no visible dots
- Cast silicone with IP67 and IK10
- Cut at 41.6 mm, bend radius 60 mm
- CRI above 90
- Omnidirectional emission
- On/off or dimming versions

Recommended applications

Facade outlines

Signage and letters

Terraces and pergolas

Steps and pool edges

Landscaping