

TECHNICAL DATASHEET · EXTERIOR ARCHITECTURAL LIGHTING - CELESTIAL SERIES

Celestial Bidirectional LED Wall Light 2x3W Outdoor

EcoSolaris code: ECO-LED-56950 · Designed and manufactured in Europe · OSRAM LEDs



Wall luminaire with bidirectional up and down emission and an elliptical optic, for accent lighting of facades. The die-cast aluminium housing integrates the power supply; IP65 protection, IK06 impact resistance, protection class I. Power 2x3 W, flux 263 lm, available in 3000 K or 4000 K.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Type	Bidirectional LED wall light
Mounting	Surface-mounted on wall, outdoor
Housing material	Die-cast aluminium
Colour	Black
Power	2x3 W
Luminous flux	263 lm
Luminous efficacy	44 lm/W
Optic	Elliptical
Colour temperature	3000 K / 4000 K
CRI	80
Control	on/off
Ingress protection	IP65
Impact resistance	IK06
Protection class	I
Driver	Included in the housing
Adjustable	No
Dimensions	165 x 94 x 48.5 mm

Features

- Simultaneous up and down emission with elliptical distribution
- Power supply integrated in the housing
- Die-cast aluminium housing, black finish
- IP65 protection against dust and water jets
- Two colour temperatures: 3000 K and 4000 K, CRI 80
- Total power 6 W, on/off control

Recommended applications

Residential facades

Entrances and columns

Guesthouses and hotels

Boundary walls

Courtyards