

TECHNICAL DATASHEET · EXTERIOR ARCHITECTURAL LIGHTING - UP&DOWN SERIES

Up&Down Bidirectional LED Wall Light 2x7.5W Outdoor

EcoSolaris code: ECO-LED-56965 · Designed and manufactured in Europe · OSRAM LEDs



Wall luminaire with up and down emission, 2x7.5 W and a wide optic, for functional lighting of facades and access areas. Flux 1652 lm, efficacy 110 lm/W, CRI above 80, available in 3000 K or 4000 K. Die-cast aluminium housing with integrated driver, IP65, IK06, protection class I.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Type	Bidirectional LED wall light
Mounting	Surface-mounted on wall, outdoor
Housing material	Die-cast aluminium
Colour	Black
Power	2x7.5 W
Luminous flux	1652 lm
Luminous efficacy	110 lm/W
Optic	Wide
Colour temperature	3000 K / 4000 K
CRI	above 80
Control	on/off
Ingress protection	IP65
Impact resistance	IK06
Protection class	I
Driver	Included in the housing
Adjustable	No
Dimensions	179 x 70 x 95 mm

Features

- Bidirectional emission with a wide optic
- 1652 lm at 15 W, 110 lm/W
- Die-cast aluminium, black finish
- Integrated driver, protection class I
- IP65 / IK06 protection for outdoor use
- 3000 K or 4000 K, CRI above 80

Recommended applications

Residential facades

Office entrances

Residential compounds

Covered walkways

Car park walls