

TECHNICAL DATASHEET · EXTERIOR ARCHITECTURAL LIGHTING - FLEXIBEAM SERIES

FlexiBeam Bidirectional LED Wall Light 2x5W Adjustable Beam

EcoSolaris code: ECO-LED-56980 · Designed and manufactured in Europe · OSRAM LEDs



Wall luminaire with two 5 W LED modules and a beam angle adjustable between 15 and 120 degrees, for residential and hospitality lighting. Aluminium housing with integrated driver, IP65 protection, IK06 impact resistance, protection class I. Flux 750-900 lm, efficacy 90 lm/W, CRI above 80, 3000 K or 4000 K.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Type	Bidirectional LED wall light, adjustable angle
Mounting	Surface-mounted on wall, outdoor
Housing material	Aluminium
Colour	Black
Power	2x5 W
Luminous flux	750-900 lm
Luminous efficacy	90 lm/W
Optic	Adjustable, 15-120 degrees
Colour temperature	3000 K / 4000 K
CRI	above 80
Control	on/off
Ingress protection	IP65
Impact resistance	IK06
Protection class	I
Driver	Included in the housing
Dimensions	120 x 96.8 x 100 mm

Features

- Beam angle adjustable 15-120 degrees per direction
- Bidirectional emission, up and down
- Integrated driver, direct mains connection
- Aluminium housing, IP65 / IK06 protection
- CRI above 80, 3000 K or 4000 K
- 90 lm/W at 2x5 W

Recommended applications

Residential facades

Hotels and guesthouses

Restaurant terraces

Pedestrian passages

Columns and pilasters