

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - OFFICE LINE SERIES

Office Line 1100 Suspended LED Luminaire 40W Indoor

EcoSolaris code: ECO-LED-56995 · Designed and manufactured in Europe · OSRAM LEDs



Suspended linear profile of 1100x25x100 mm in anodised black aluminium, emitting light upwards and downwards. 40 W, 2638 lm, wide optic, 4000 K, CRI 90, SDCM under 3 (ANSI). 24 V DC supply, driver not included. IP20, insulation class I.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Suspended
Material	Anodised aluminium
Colour	RAL9010 anodised black
Power	40 W
Luminous flux	2638 lm
Luminous efficacy	66 lm/W
Light direction	Up and down
Optic	Wide
Colour temperature	4000 K
CRI	90
Colour consistency	SDCM under 3 (ANSI)
Control	on/off
Ingress protection	IP20
Insulation class	I
Power supply	24 V DC, driver not included
Dimensions	1100x25x100 mm

Features

- Direct and indirect emission (up and down)
- CRI 90 and SDCM under 3 for colour uniformity
- Slim profile only 25 mm wide
- 24 V DC supply
- Anodised black finish
- IP20, insulation class I

Recommended applications

Open-plan offices

Meeting rooms

Receptions

Libraries

Coworking spaces