

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - SMOOTH SERIES

Smooth A Linear LED System 34W Wall Washer

EcoSolaris code: ECO-LED-57048 · Designed and manufactured in Europe · OSRAM LEDs



Linear ceiling profile of 1500x44.8x83 mm in black aluminium, with asymmetric wall washer distribution. 34 W, 3888 lm, 115 lm/W, CRI 90, 3000 K or 4000 K. Integral power supply, 220-240 V AC. IP20, insulation class I.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Surface ceiling mounted
Material	Aluminium
Colour	RAL9010 black
Power	34 W
Luminous flux	3888 lm
Luminous efficacy	115 lm/W
Light distribution	Asymmetric, wall washer
Colour temperature	3000 K / 4000 K
CRI	90
Control	on/off
Ingress protection	IP20
Insulation class	I
Power supply	220-240 V AC, driver included
Dimensions	1500x44.8x83 mm
Adjustable	No

Features

- Asymmetric wall washer optic for a single wall
- Length of 1500 mm, aligns in a continuous line
- 3888 lm at 34 W, efficacy of 115 lm/W
- Driver included, 220-240 V AC
- CRI 90
- IP20, insulation class I

Recommended applications

Art galleries Showrooms Hotel receptions Office lobbies Retail display walls