

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - SMOOTH SERIES

Smooth 2A Linear LED System 34W Double Asymmetric

EcoSolaris code: ECO-LED-57063 · Designed and manufactured in Europe · OSRAM LEDs



Linear ceiling profile of 1500x44.8x83 mm in black aluminium, with double asymmetric light distribution. 34 W, 3040 lm, CRI 90, colour temperature 3000 K or 4000 K. Integral power supply, 220-240 V AC. IP20, insulation class I.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Surface ceiling mounted
Material	Aluminium
Colour	RAL9010 black
Power	34 W
Luminous flux	3040 lm
Light distribution	Double asymmetric
Colour temperature	3000 K / 4000 K
CRI	90
Control	on/off
Ingress protection	IP20
Insulation class	I
Power supply	220-240 V AC, driver included
Dimensions	1500x44.8x83 mm
Adjustable	No

Features

- Double asymmetric optic for two vertical surfaces
- Length of 1500 mm, aligns end to end
- CRI 90 for faithful colour rendering
- Driver included, 220-240 V AC
- Profile 44.8 mm wide, black finish
- IP20, insulation class I

Recommended applications

Bookshop and store shelving

Hotel corridors

Pharmacies

Archives

Galleries with display walls