

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - ECLIPSAR SERIES

Eclipsar Suspended LED Luminaire 15W Indoor

EcoSolaris code: ECO-LED-57078 · Designed and manufactured in Europe · OSRAM LEDs



Cylindrical LED pendant of 63 x 300 mm, 15 W, flux 1,252 lm (narrow optic) or 1,360 lm (wide optic), efficacy 83-92 lm/W, CCT 3000/4000 K, CRI 90. Black aluminium housing, power supply included, IP20, class I, suspended mounting, fixed emission.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Suspended
Housing material	Aluminium
Finish	Black (RAL9010)
Power	15 W
Luminous flux	1,252 - 1,360 lm
Luminous efficacy	83 - 92 lm/W
Available optics	Narrow, wide
Colour temperature	3000 K / 4000 K
CRI	90
Control	On/off
Ingress protection	IP20
Insulation class	I
Driver	Included
Adjustable	No
Dimensions	63 x 300 mm

Features

- Slim cylindrical pendant, 63 x 300 mm
- 15 W with flux up to 1,360 lm
- Narrow and wide optics
- CRI 90
- Power supply included
- Class I, IP20, suspended mounting

Recommended applications

Restaurant tables

Bars and counters

Receptions

Kitchen islands

Private workstations