

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - INVISILUX SERIES

Invisilux W Adjustable Recessed LED Spotlight 12W

EcoSolaris code: ECO-LED-57112 · Designed and manufactured in Europe · OSRAM LEDs



Adjustable recessed LED spotlight, 12 W, 1164 lm, 89.5 lm/W, wide 38 degree beam, CRI 90. White RAL9010 aluminium housing, 86 x 94 mm, IP40, class III, driver included and mounted externally, power factor above 0.9. CCT 3000 K or 4000 K, supply 220-240 V AC.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Recessed in ceiling
Material	Aluminium
Colour	White RAL9010
Power	12 W
Luminous flux	1164 lm
Luminous efficacy	89.5 lm/W
Optical efficiency	89 %
Optic	Wide, 38 degrees
CCT	3000 K / 4000 K
CRI	90
Power factor	> 0.9
Control	on/off
Supply voltage	220 - 240 V AC
Ingress protection	IP40
Electrical class	III
Driver included	Yes, outside the housing
Adjustable	Yes
Dimensions	86 x 94 mm

Features

- 38 degree beam for wall and object accents
- CRI 90
- Body adjustable after installation
- 1164 lm from 12 W
- Power factor above 0.9
- Driver included, IP40, class III

Recommended applications

Homes

Offices and meeting rooms

Shops

Cafes

Hallways