

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - INVISILUX SERIES

Invisilux T Adjustable Recessed LED Spotlight 10W CRI97

EcoSolaris code: ECO-LED-57127 · Designed and manufactured in Europe · OSRAM LEDs



Adjustable recessed LED spotlight, 10 W, CRI 97, with 15, 24 or 60 degree optics and flux of 929-1027 lm. White RAL9010 aluminium housing, 90 x 69 mm, IP44, class III, driver included and mounted externally, power factor above 0.9. CCT 3000 K or 4000 K, supply 220-240 V AC.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Recessed in ceiling
Material	Aluminium
Colour	White RAL9010
Power	10 W
Luminous flux	929 - 1027 lm
Luminous efficacy	88 - 97 lm/W
Optical efficiency	84.5 - 89.1 %
Available optics	Narrow 15, medium 24, wide 60 degrees
CCT	3000 K / 4000 K
CRI	97
Power factor	> 0.9
Control	on/off
Supply voltage	220 - 240 V AC
Ingress protection	IP44
Electrical class	III
Driver included	Yes, outside the housing
Adjustable	Yes
Dimensions	90 x 69 mm

Features

- CRI 97 for faithful colour rendering
- Three beam angles: 15, 24, 60 degrees
- Head adjustable after installation
- IP44 protection
- Power factor above 0.9
- Driver included, class III, 220-240 V AC

Recommended applications

Art galleries and museums

Boutiques and jewellery stores

Restaurants

Finishes showrooms

Cosmetics stores

