

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - INVISILUX SERIES

Invisilux D Recessed LED Spotlight 8W IP54

EcoSolaris code: ECO-LED-57173 · Designed and manufactured in Europe · OSRAM LEDs



Fixed recessed LED downlight, 8 W, 635 lm, 80 lm/W, with a wide 60 degree beam. Aluminium housing in white RAL9010 or black, 106 x 84 mm, integrated driver. IP54 below the ceiling and IP20 inside the ceiling, class II. CCT 3000 K or 4000 K, CRI 80, supply 220-240 V AC.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Recessed in ceiling
Material	Aluminium
Available colours	White RAL9010, black
Power	8 W
Luminous flux	635 lm
Luminous efficacy	80 lm/W
Optical efficiency	87 %
Optic	Wide, 60 degrees
CCT	3000 K / 4000 K
CRI	80
Control	on/off
Supply voltage	220 - 240 V AC
Ingress protection	IP54 below ceiling, IP20 inside ceiling
Electrical class	II
Driver included	Yes, integrated in the housing
Adjustable	No
Dimensions	106 x 84 mm

Features

- Exposed face protected to IP54 for humid rooms
- Wide 60 degree beam for even light
- Driver integrated in the housing
- White or black finish
- Compact body of 106 x 84 mm
- Supply 220-240 V AC, class II

Recommended applications

Bathrooms

Kitchens

Changing rooms and laundries

Hallways and dressing rooms

Service corridors