

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - FLEXIRAY SERIES

Flexiray S Adjustable Recessed LED Spotlight 10W

EcoSolaris code: ECO-LED-57192 · Designed and manufactured in Europe · OSRAM LEDs



Adjustable recessed LED downlight, 10 W, 1096 lm, 119 lm/W, with a medium 30 degree optic. Aluminium housing in white RAL9010 or black, 81 x 131.5 mm. CCT 3000 K or 4000 K, CRI 80, SDCM below 5. Supply 220-240 V AC, driver included and mounted externally, IP20, class II.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Recessed in ceiling
Material	Aluminium
Available colours	White RAL9010, black
Power	10 W
Luminous flux	1096 lm
Luminous efficacy	119 lm/W
Optical efficiency	89 %
Optic	Medium, 30 degrees
CCT	3000 K / 4000 K
CRI	80
Colour consistency	SDCM < 5 (ANSI)
Control	on/off
Supply voltage	220 - 240 V AC
Ingress protection	IP20
Electrical class	II
Driver included	Yes, outside the housing
Adjustable	Yes
Dimensions	81 x 131.5 mm

Features

- 30 degree beam for precise accents
- Body adjustable after installation
- 1096 lm from 10 W, 119 lm/W
- White or black finish
- SDCM below 5 for even tint
- Driver included, IP20, class II

Recommended applications

Homes

Offices and consulting rooms

Cafes

Convenience stores

Hallways and corridors