

TECHNICAL DATASHEET · EXTERIOR ARCHITECTURAL LIGHTING - ARCADIA SERIES

Arcadia D Surface-Mounted LED Spotlight 15W IP54 Outdoor

EcoSolaris code: ECO-LED-57253 · Designed and manufactured in Europe · OSRAM LEDs



Surface-mounted ceiling LED spotlight, 15 W, rated IP54 for covered damp areas. Flux 1418-1502 lm, efficacy 108-113 lm/W, CRI 90, narrow, medium or wide optics, 3000 K or 4000 K. Black aluminium housing, driver included, 220-240 V AC, 120 x 110 mm.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Surface-mounted on ceiling
Material	Aluminium
Colour	Black
Power	15 W
Luminous flux	1418-1502 lm
Luminous efficacy	108-113 lm/W
Optical efficiency	89 %
Available optics	Narrow, medium, wide
Colour temperature	3000 K / 4000 K
CRI	90
Control	on/off
Supply	220-240 V AC, driver included
Protection class	I
Ingress protection	IP54
Dimensions	120 x 110 mm
Adjustable	No

Features

- IP54 for terraces, walkways and bathrooms
- 1418-1502 lm at 15 W
- Efficacy 108-113 lm/W
- CRI 90
- Three optics: narrow, medium, wide
- Driver in the housing, class I

Recommended applications

Covered terraces

Pedestrian walkways

Building entrances

Bathrooms

Hotels and restaurants