

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - LALUNA SERIES

Laluna Magnetic Track Decorative LED Luminaire 5W

EcoSolaris code: ECO-LED-57306 · Designed and manufactured in Europe · OSRAM LEDs



Decorative 5 W LED luminaire for a 48 V DC low-voltage magnetic track, with omnidirectional emission of 617 lm and efficacy of 100 lm/W. CRI above 90, SDCM below 3, 3000 K or 4000 K. Black anodised aluminium, 100 x 170 x 1200 mm, class III, IP20. Driver not included.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Magnetic, on 48 V DC track
Material	Anodised aluminium
Colour	Black
Power	5 W
Luminous flux	617 lm
Luminous efficacy	100 lm/W
Luminous efficiency	70 %
Optic	Omnidirectional
Colour temperature	3000 K / 4000 K
CRI	> 90
Colour consistency	SDCM < 3 (light source)
Control	on/off
Power supply	48 V DC, driver not included
Electrical class	III
Ingress protection	IP20
Dimensions	100 x 170 x 1200 mm
Accessory	Surface-mounted 48 V DC magnetic track, 3 m

Features

- Omnidirectional emission for ambient light
- 617 lm at 5 W, 100 lm/W
- CRI above 90, SDCM below 3
- Magnetic coupling on 48 V DC track
- Black anodised aluminium
- Class III, IP20

Recommended applications

Restaurants and cafes

Hotel receptions and lobbies

Living rooms and bedrooms