

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - 48V MAGNETIC TRACK SYSTEM - ZOOMIX SERIES

Zoomix Adjustable LED Spotlight 12W for 48V Magnetic Track

EcoSolaris code: ECO-LED-57321 · Designed and manufactured in Europe · OSRAM LEDs



Adjustable aluminium spotlight, 65 x 135 x 55.5 mm, for 48 V DC magnetic track, with a zoom optic adjustable between 15 and 36 degrees. Power 12 W, flux 977 lm, efficacy 62 lm/W, CRI 90, SDCM below 5 steps, colour temperature 3000 K or 4000 K. On/off control, insulation class III, IP20; powered through the track, with a 3 m surface track available as an accessory.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	48 V DC magnetic track, adjustable head
Material	Aluminium
Finish	Black
Power	12 W
Luminous flux	977 lm
Luminous efficacy	62 lm/W
Optic	Zoom, adjustable 15-36 degrees
Colour temperature	3000 K / 4000 K
CRI	90
Colour consistency	SDCM < 5 steps (ANSI)
Supply voltage	48 V DC
Control	on/off
Ingress protection	IP20
Insulation class	III
Driver included	No
Accessory	Surface-mounted 48 V DC magnetic track, 3 m
Dimensions	65 x 135 x 55.5 mm

Features

- Zoom optic 15-36 degrees, set by hand
- Tilting head, magnetic coupling to the track
- 977 lm from 12 W
- CRI 90 and SDCM below 5 steps
- 48 V DC supply, insulation class III
- Aluminium body, black finish

Recommended applications

Shops and retail

Galleries and museums

Showrooms

Restaurants

Homes with track lighting