

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - 48 V MAGNETIC TRACK SYSTEM

Luminesse Magnetic Track LED Luminaire 48V 20W

EcoSolaris code: ECO-LED-57355 · Designed and manufactured in Europe · OSRAM LEDs



Linear module of 900x23x40.8 mm in black aluminium, held magnetically on 48 V DC track. 20 W, 1357 lm, omnidirectional 100 degrees distribution, CRI 90, SDCM under 3 Step (ANSI), 3000 K or 4000 K. Insulation class III, IP20. The power supply and the track are not included.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	48 V DC magnetic track
Material	Aluminium
Colour	RAL9010 black
Power	20 W
Luminous flux	1357 lm
Luminous efficacy	70 lm/W
Light distribution	Omnidirectional, 100 degrees
Colour temperature	3000 K / 4000 K
CRI	90
Colour consistency	SDCM under 3 Step (ANSI)
Control	on/off
Ingress protection	IP20
Insulation class	III
Power supply	48 V DC, driver not included
Dimensions	900x23x40.8 mm
Accessory	Surface-mounted 48 V DC magnetic track, 3 m

Features

- Magnetic fixing, repositioning without tools
- 100 degrees distribution for general light
- CRI 90 and SDCM under 3
- Low voltage 48 V DC, class III
- Profile only 23 mm wide
- Works with the 3 m surface-mounted track

Recommended applications

Living rooms and kitchens

Offices

Clinics

Shops

Magnetic track interiors