

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - RORY SERIES

Rory Low Voltage 48V Magnetic Track LED Spotlight 10W

EcoSolaris code: ECO-LED-57370 · Designed and manufactured in Europe · OSRAM LEDs



LED spotlight for surface 48 V DC magnetic track, 10 W, 838 lm, 61 lm/W, 24 degrees light distribution, CCT 3000/4000 K, CRI 90, SDCM below 5 steps (ANSI). Aluminium housing of 52 x 120 mm, IP20, class III, tilting head, no driver on board. A 3 m surface magnetic track is available as an accessory.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Surface 48 V DC magnetic track
Housing material	Aluminium
Finish	Black (RAL9010)
Power	10 W
Luminous flux	838 lm
Luminous efficacy	61 lm/W
Optic	Medium, 24 degrees
Colour temperature	3000 K / 4000 K
CRI	90
Colour consistency	SDCM below 5 steps (ANSI)
Control	On/off
Supply voltage	48 V DC
Ingress protection	IP20
Insulation class	III
Driver	Not included
Adjustable	Yes
Available accessories	Surface 48 V DC magnetic track, 3 m
Dimensions	52 x 120 mm

Features

- Magnetic mounting, repositioned without tools
- 48 V DC supply, insulation class III
- 10 W, 838 lm, 24 degrees beam
- CRI 90, SDCM below 5 steps
- Compact aluminium body, 52 x 120 mm
- Tilting head on the track

Recommended applications

Living rooms and kitchens

Corridors

Offices

Small shops

Surface magnetic track systems