

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - SLIM MAGNETIC TRACK SYSTEM

Noglo F LED Spotlight Slim Magnetic Track 6W

EcoSolaris code: ECO-LED-57488 · Designed and manufactured in Europe · OSRAM LEDs



Fixed spotlight of 80x75 mm in black aluminium for 48 V DC slim magnetic track. 6 W, 363 lm, 60.5 lm/W, medium optic, CRI 90, 3000 K or 4000 K. Insulation class III, IP20. The power supply is not included.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	48 V DC slim magnetic track
Material	Aluminium
Colour	RAL9010 black
Power	6 W
Luminous flux	363 lm
Luminous efficacy	60.5 lm/W
Optic	Medium
Colour temperature	3000 K / 4000 K
CRI	90
Control	on/off
Ingress protection	IP20
Insulation class	III
Power supply	48 V DC, driver not included
Dimensions	80x75 mm
Accessory	48 V DC slim magnetic track
Adjustable	No

Features

- Compact fixed head, 80x75 mm
- 6 W, 363 lm, medium optic
- CRI 90
- Magnetic fixing on slim track
- Low voltage 48 V DC, class III
- Black finish

Recommended applications

Kitchens and hallways

Dressing rooms

Cafes

Jewellery and cosmetics shops

Display windows