

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - SLIM MAGNETIC TRACK SYSTEM

Noglo T Adjustable LED Spotlight Slim Magnetic Track 10W

EcoSolaris code: ECO-LED-57503 · Designed and manufactured in Europe · OSRAM LEDs



Adjustable spotlight of 44x112 mm in black aluminium for 48 V DC slim magnetic track. 10 W, 702 lm, 64 lm/W, medium optic, CRI 90, 3000 K or 4000 K. Insulation class III, IP20. The power supply and the track are not included.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	48 V DC slim magnetic track, adjustable
Material	Aluminium
Colour	RAL9010 black
Power	10 W
Luminous flux	702 lm
Luminous efficacy	64 lm/W
Optic	Medium
Colour temperature	3000 K / 4000 K
CRI	90
Control	on/off
Ingress protection	IP20
Insulation class	III
Power supply	48 V DC, driver not included
Dimensions	44x112 mm
Accessory	48 V DC slim magnetic track
Adjustable	Yes

Features

- Aimable after mounting
- 10 W, 702 lm, medium optic
- CRI 90
- Compact body of 44x112 mm
- Magnetic fixing, 48 V DC, class III
- Black finish

Recommended applications

Artwork and objects

Product shelves

Restaurants

Small galleries

Homes with slim track