

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - SLIM MAGNETIC TRACK SYSTEM

Noglo P Linear LED Module Slim Magnetic Track 6W

EcoSolaris code: ECO-LED-57526 · Designed and manufactured in Europe · OSRAM LEDs



Linear module of 30x300 mm in black aluminium for 48 V DC slim magnetic track. 6 W, 400 lm, 66.6 lm/W, medium optic, CRI 90, 3000 K or 4000 K. Insulation class III, IP20. The power supply and the track are not included.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	48 V DC slim magnetic track
Material	Aluminium
Colour	RAL9010 black
Power	6 W
Luminous flux	400 lm
Luminous efficacy	66.6 lm/W
Optic	Medium
Colour temperature	3000 K / 4000 K
CRI	90
Control	on/off
Ingress protection	IP20
Insulation class	III
Power supply	48 V DC, driver not included
Dimensions	30x300 mm
Accessory	48 V DC slim magnetic track
Adjustable	No

Features

- Linear module of 300 mm, aligns along the track
- Width of 30 mm
- 6 W, 400 lm, medium optic
- CRI 90
- Magnetic fixing, 48 V DC, class III
- Black finish

Recommended applications

Kitchens

Corridors

Bedrooms

Small offices

Shops