

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - ASTRALINE SERIES - SLIM MAGNETIC TRACK

Astraline M Linear LED Luminaire 20W for Slim Magnetic Track

EcoSolaris code: ECO-LED-57633 · Designed and manufactured in Europe · OSRAM LEDs



Diffuse linear luminaire of 615 mm for slim 48 V DC magnetic track, with omnidirectional 100 degree emission for ambient lighting in offices, retail, museums and hospitality. Power 20 W, flux 1298 lm, 65 lm/W, CRI 90, 3000 K or 4000 K. Black aluminium, IP20, class III, power supply not included.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Type	Linear LED luminaire for slim magnetic track
Mounting	On slim magnetic track, indoor
Material	Aluminium
Colour	Black
Power	20 W
Luminous flux	1298 lm
Luminous efficacy	65 lm/W
Optic	Omnidirectional, 100 degrees
Colour temperature	3000 K / 4000 K
CRI	90
Control	on/off
Supply	48 V DC through the track, supply not included
Ingress protection	IP20
Protection class	III
Driver	Not included
Accessories	Slim magnetic track 48 V DC
Dimensions	615 x 24 x 26 mm

Features

- Diffuse omnidirectional light, 100 degree beam
- Tool-free mounting and repositioning on slim magnetic track
- CRI 90 for natural colour rendering
- Slim 24 x 26 mm section, 615 mm long
- 48 V DC supply, protection class III
- 3000 K or 4000 K, 20 W

Recommended applications

Offices

Retail spaces

Museums

Hotels and receptions

Homes