

TECHNICAL DATASHEET · EXTERIOR ARCHITECTURAL LIGHTING - WINDOW LED FLOODLIGHTS - HELIOS SERIES

Helios Window LED Floodlight 5-7.6W Outdoor

EcoSolaris code: ECO-LED-57789 · Designed and manufactured in Europe · OSRAM LEDs



Compact polycarbonate facade floodlight, 130 x 90 x 55 mm, with an elliptical optic for outlining windows and niches. Three power versions (5 W, 7.5 W, 7.6 W) with 481-893 lm and efficacy up to 119 lm/W. Power supply built into the housing, IP67/IK9 protection, on/off, 1-10V or DALI control; coloured LEDs on request.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Surface mounted, fixed
Material	Polycarbonate
Finish	Black
Power	5 W / 7.5 W / 7.6 W
Luminous flux	481-893 lm
Luminous efficacy	97-119 lm/W
Optic	Elliptical
Colour temperature	3000 K / 4000 K / 5000 K; coloured LEDs on request
CRI	80
Control	on/off, 1-10V, DALI
Ingress protection	IP67 / IK9
Insulation class	II (general datasheet) / III (variant table)
Driver included	Yes, integral power supply
Dimensions	130 x 90 x 55 mm

Features

- Elliptical optic covering window surrounds across their width
- IP67 and IK9 protection for outdoor use
- Efficacy up to 119 lm/W (7.5 W version)
- Power supply integrated in the housing
- Three colour temperatures, coloured LEDs on request
- On/off, 1-10V or DALI control

Recommended applications

Windows and surrounds

Facade niches

Cornices

Offices and hotels

Heritage buildings