

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - RECESSED LED SPOTLIGHTS - PLUTO SERIES

Pluto Orbit Mini Adjustable Recessed LED Spotlight 4W

EcoSolaris code: ECO-LED-61936 · Designed and manufactured in Europe · OSRAM LEDs



Recessed accent spotlight with a tilting head, 4 W and 52 x 25 mm, in aluminium with a polycarbonate diffuser. Narrow, medium or wide optic, flux 194-327 lm, CRI above 90, colour temperature 3000 K (other CCTs or coloured LEDs on request). Extra-low voltage supply, class III, driver included, LED lifetime 100,000 hours L80.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Recessed, adjustable
Material	Aluminium, polycarbonate diffuser
Finish	Grey RAL7040
Power	4 W
Luminous flux	194-327 lm (depending on optic)
Luminous efficacy	53-82 lm/W
Optics	Narrow, medium, wide
Colour temperature	3000 K; other CCTs or coloured LEDs on request
CRI	> 90
Control	on/off
Supply	Extra-low voltage, driver included
Ingress protection	IP20
Insulation class	III
LED lifetime	100,000 hours (L80)
Dimensions	52 x 25 mm

Features

- Tilting head for aiming the beam after installation
- Ultra-compact body, 52 x 25 mm
- Three optics: narrow, medium, wide
- CRI above 90, warm white 3000 K
- Extra-low voltage, insulation class III
- 100,000 hours L80, quick recessing system

Recommended applications

Paintings and artwork

Decorative niches

Display cases and joinery

Galleries and shops

Homes and hotels