

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - RECESSED LED SPOTLIGHTS - PLUTO SERIES

Pluto Core Mini Recessed LED Spotlight 4W

EcoSolaris code: ECO-LED-61975 · Designed and manufactured in Europe · OSRAM LEDs



Miniature recessed spotlight, 4 W, 40 x 26 mm and 0.048 kg, with a grey aluminium body and clear polycarbonate diffuser. Narrow, medium or wide optic, flux 194-327 lm, CRI above 90, warm white 3000 K (other CCTs or coloured LEDs on request). Runs at extra-low voltage, class III, with the driver included; LED lifetime 100,000 hours L80.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Recessed, fixed
Material	Aluminium, clear polycarbonate diffuser
Finish	Grey RAL7040
Power	4 W
Luminous flux	194-327 lm (depending on optic)
Luminous efficacy	53-82 lm/W
Optics	Narrow, medium, wide
Colour temperature	3000 K; other CCTs or coloured LEDs on request
CRI	> 90
Control	on/off
Supply	Extra-low voltage, driver included
Ingress protection	IP20
Insulation class	III
LED lifetime	100,000 hours (L80)
Dimensions	40 x 26 mm
Weight	0.048 kg

Features

- Compact 40 x 26 mm format for niches and joinery
- Three optics: narrow, medium, wide
- CRI above 90
- Warm white 3000 K as standard
- Extra-low voltage, insulation class III
- 100,000 hours L80

Recommended applications

Niches and coves

Joinery and bookcases

Display cases

Hotel receptions

Homes