

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - ARVIO SERIES

Arvio 4 Multi-Prismatic Linear LED Luminaire 44W

EcoSolaris code: ECO-LED-62787 · Designed and manufactured in Europe · OSRAM LEDs



Linear luminaire of 1198 mm in extruded aluminium, with an anti-glare multi-prismatic diffuser for offices and retail. Power 44 W, flux 5258 lm, efficacy 103 lm/W, 4000 K, CRI 80 or above 90. Surface or suspended mounting, IP20, IK10, class I, driver included, compatible with DALI and 1-10V.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Type	Linear LED luminaire, multi-prismatic diffuser
Mounting	Surface / suspended
Material	Extruded aluminium
Colours	White RAL 9010 / Black
Power	44 W
Luminous flux	5258 lm
Luminous efficacy	103 lm/W
Optic	Multi-prismatic anti-glare
Colour temperature	4000 K
CRI	80 / above 90
Control	on/off; DALI and 1-10V compatible
Ingress protection	IP20
Impact resistance	IK10
Protection class	I
Driver	Included
Accessories	Fixing clamp
Dimensions	1198 x 57 x 44 mm

Features

- Anti-glare multi-prismatic diffuser for visual comfort
- Even emission with no shadow gaps
- 5258 lm at 44 W, 103 lm/W
- Surface or suspended mounting
- Extruded aluminium profile, IK10
- Compatible with DALI and 1-10V control
- Two CRI options: 80 and above 90

Recommended applications

Open-plan offices

Meeting rooms

Classrooms

Libraries

Corridors

Retail spaces