

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - ARVIO SERIES

Arvio 5 Multi-Prismatic Linear LED Luminaire 55W

EcoSolaris code: ECO-LED-62806 · Designed and manufactured in Europe · OSRAM LEDs



Linear luminaire of 1496 mm in extruded aluminium with an anti-glare multi-prismatic diffuser, for offices, institutions and retail. Power 55 W, flux 6573 lm, 103 lm/W, 4000 K, CRI 80 or above 90. Surface or suspended mounting, IP20, IK10, class I, driver included, compatible with DALI and 1-10V.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Type	Linear LED luminaire, multi-prismatic diffuser
Mounting	Surface / suspended
Material	Extruded aluminium
Colours	White RAL 9010 / Black
Power	55 W
Luminous flux	6573 lm
Luminous efficacy	103 lm/W
Optic	Multi-prismatic anti-glare
Colour temperature	4000 K
CRI	80 / above 90
Control	on/off; DALI and 1-10V compatible
Ingress protection	IP20
Impact resistance	IK10
Protection class	I
Driver	Included
Accessories	Fixing clamp
Dimensions	1496 x 57 x 44 mm

Features

- Length 1496 mm for continuous lines of light
- Anti-glare multi-prismatic diffuser
- 6573 lm at 55 W, 103 lm/W
- Surface mounting with clamp or suspended
- Extruded aluminium, IK10, class I
- Compatible with DALI and 1-10V systems
- CRI 80 or above 90, 4000 K

Recommended applications

High-ceiling offices

Conference rooms

Lecture theatres

Laboratories

Sales halls

Long corridors