

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - LINEAR SYSTEMS - UNOLUCE SERIES

Unoluce Suspended Linear LED System 18.4W for Offices

EcoSolaris code: ECO-LED-63579 · Designed and manufactured in Europe · OSRAM LEDs

Suspended 18.4 W linear luminaire for offices, with UGR below 10 and CRI above 90. Extruded aluminium body of 1080 x 26 x 72.5 mm in white or black, with a lens and plastic screen diffuser. Narrow, medium, wide or honeycomb optics, 690-1576 lm, 4000 K standard or 3000 K optional. On/off or DALI control, driver and suspension kit included, LEDs rated 150,000 hours L80.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Mounting type	Suspended (pendant), fixing system included
Material	Extruded aluminium, lens diffuser with plastic screen
Available finishes	White RAL9010, black
Power	18.4 W
Luminous flux	690-1576 lm (depending on optic)
Luminous efficacy	38-86 lm/W
Optics	Narrow, medium, wide, honeycomb
Colour temperature	4000 K standard; 3000 K optional
CRI	> 90
UGR	< 10
Control	on/off, DALI
Ingress protection	IP20
Insulation class	I
Driver included	Yes
LED lifetime	150,000 hours (L80)
Dimensions	1080 x 26 x 72.5 mm

Features

- UGR below 10 for screen-based workstations
- CRI above 90
- Narrow, medium, wide or honeycomb optics
- DALI or on/off control
- 150,000 hours L80
- 26 mm wide profile, white or black
- Driver and suspension kit included

Recommended applications

Offices

Open-plan floors

Meeting rooms

Libraries

Study areas