

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - ARCADIA SERIES

Arcadia R Adjustable Surface-Mounted LED Spotlight 15W

EcoSolaris code: ECO-LED-64315 · Designed and manufactured in Europe · OSRAM LEDs



Surface-mounted ceiling spotlight with an adjustable head, 15 W, medium 36 degree optic, for accent lighting in retail and residential projects. Flux 1709 lm, efficacy 123 lm/W, CRI 90, available in 3000 K or 4000 K. Aluminium housing in white RAL 9010 or black, driver included, IP20, class I.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Type	Surface-mounted LED spotlight, adjustable
Mounting	Surface-mounted on ceiling, indoor
Housing material	Aluminium
Colours	White RAL 9010 / Black
Power	15 W
Luminous flux	1709 lm
Luminous efficacy	123 lm/W
Optic	Medium, 36 degrees
Colour temperature	3000 K / 4000 K
CRI	90
Control	on/off
Ingress protection	IP20
Protection class	I
Driver	Included
Adjustable	Yes
Dimensions	186 x 85 mm

Features

- Adjustable head for aiming after installation
- Medium 36 degree optic for precise accents
- 1709 lm at 15 W, 123 lm/W
- CRI 90, 3000 K or 4000 K
- Two finishes: white RAL 9010 and black
- Driver included, class I, IP20

Recommended applications

Shops and displays Showrooms Art galleries Restaurants Homes