

TECHNICAL DATASHEET · INTERIOR ARCHITECTURAL LIGHTING - ARCADIA SERIES

Arcadia L Surface-Mounted LED Spotlight 10W Interchangeable Optics

EcoSolaris code: ECO-LED-64338 · Designed and manufactured in Europe · OSRAM LEDs



Cylindrical surface-mounted ceiling spotlight, 100 x 70 mm, 10 W, with interchangeable optics: medium, wide, extra wide, wall washer and double asymmetric. Flux 933-1020 lm, efficacy 97-107 lm/W, CRI 90, 3000 K. White RAL 9010 aluminium housing, driver included, IP20, protection class I.

Price on request

Minimum order 10 pcs

Made to order

EcoSolaris technical support

Technical specifications

Type	Surface-mounted cylindrical LED spotlight
Mounting	Surface-mounted on ceiling, indoor
Housing material	Aluminium
Colour	White RAL 9010
Power	10 W
Luminous flux	933-1020 lm
Luminous efficacy	97-107 lm/W
Available optics	Medium / Wide / Extra wide / Wall washer / Double asymmetric
Colour temperature	3000 K
CRI	90
Control	on/off
Ingress protection	IP20
Protection class	I
Driver	Included
Adjustable	No
Dimensions	100 x 70 mm

Features

- Five interchangeable optics for accent, general or wall washing
- CRI 90 and 3000 K for faithful colour rendering
- Up to 107 lm/W at 10 W
- Minimal cylindrical design, no ceiling cut-out
- Driver included, direct mains connection, class I
- White RAL 9010 aluminium housing

Recommended applications

Homes

Retail spaces

Showrooms

Galleries

Hotel lobbies

Offices